

HP Latex 260 Printer

Expand your offerings with fast and easy turnarounds



Unrivaled application versatility¹

- Print on a broad range of media from vinyl, textiles,² paper, film, wallpaper to low-cost uncoated options.
- Seize your share of the growing temporary textiles market—print on a wider variety of textiles.²
- Meet client needs for sharp, vivid indoor and outdoor signs—from retail ad campaigns to interior decoration.
- See outdoor durability better than eco-solvent inks;³ offer vehicle graphics with the 3M™ MCS™ Warranty.⁴

Easy, convenient printing

- Enjoy an extremely short time to delivery—prints are dry and ready to finish or use immediately.
- Produce double-sided prints⁵ with automated registration across sides that move immediately to finishing.
- Take advantage of increased uptime that comes from automatic, reliable, low-maintenance printing.
- Use proactive alerts and accurate cost reporting to reduce interruptions and provide price quotes.

For more information, please visit hp.com/go/Latex260

Find a comprehensive list of all latex compatible media along with finished color profiles and printer settings at hp.com/go/mediasolutionslocator

Attract business from environmentminded clients

- Attract environmentally conscious customers using HP Latex Inks and recyclable HP printing materials.⁶
- Improve the work environment—no special ventilation,⁷ no hazard warning labels—unlike most eco-solvent inks.
- Return and recycle supplies for free⁸ and dramatically improve ink efficiency.⁹
- HP Latex Inks—UL ECOLOGO, GREENGUARD Children & Schools CertifiedSM,¹⁰ Eco Mark-Certified ink cartridges.¹¹
- The HP Latex 260 Printer produces an extremely broad range of both outdoor and indoor applications from a single device, which surpasses the number of different applications that traditional eco-solvent printers or water-based printers can produce.
- For best results, print on media that does not let the ink trespass onto the printer. Performance may vary depending on media. Please consult your media supplier for compatibility details.
- ³ Durability comparison based on testing of representative eco-solvent inks including eco-sol Max inks on Avery SA vinyl for display permanence and scratch, rub/abrasion, and chemical resistance. HP image permanence and scratch, smudge, and water resistance estimates by HP Image Permanence Lab on a range of media including HP printing materials.
- The 3M™ MCS™ Warranty is available to certified Graphics Manufacturers. For more information on registration and qualification requirements, refer to 3Mgraphics.com, or contact your 3M representative.
- ⁵ For best results use media options intended for double-sided printing.
- ⁶ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See <u>hp.com/recycle</u> for details.
- Poperial ventilation is not required to meet U.S. OSHA requirements on occupational exposure to VOCs from HP Latex Inks. Special ventilation equipment installation is at the discretion of the customer—no specific HP recommendation is intended. Customers should consult state and local requirements and regulations.
- Visit hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your area. Where this program is not available, consult the Material Safety Data Sheet (MSDS) available at hp.com/go/ecodata to determine appropriate disposal.
- 9 Per internal HP testing based on the amount of ink used during the recommended ink maintenance routines comparing the HP Latex Ink printing system to certain eco-solvent ink systems.
- UL ECOLOGO Certification to UL 2801 demonstrates that an ink meets a range of stringent criteria related to human health and environmental considerations (see <u>ul.com/EL</u>). HP Latex Inks are GREENGUARD Children and Schools CertifiedSM (see <u>greenguard.org</u>).
- ¹¹ HP 792 Latex Ink Cartridges, certification number 11 142 004, certified by the Eco Mark Office of Japan Environment Association.



HP Latex Printing Technologies

HP Latex Inks are water-based inks that combine the best characteristics of solvent inks and water-based inks. You can obtain the outdoor durability and versatility, across all common media types used in sign and display applications, together with high quality, odorless prints, low maintenance, and the environmental advantages of water-based inks.

Prints made with HP Latex Inks are completely cured inside the printer to form a durable image that's ready for lamination, finishing, shipment, or display.



Point of purchase posters Reduce costs without

compromising quality

 Great results on all types of paper, including lowcost uncoated papers and traditional offset papers



Light boxes

Deliver high-value backlit applications

- Produce high-resolution prints up to 1200 dpi
- Vibrant, saturated colors
- Choose from a range of backlit printing materials: paper, film, polypropylene, and textiles¹³



Outdoor and event banners

Produce images worthy of building the best brands

- Achieve high-quality results on self-adhesive vinyls and banners
- Offer outdoor display permanence up to three years unlaminated, five years laminated¹⁴



Vehicle wraps and graphics

Achieve fast turnarounds, even on urgent jobs

- Laminate right after printing—no need to wait for prints to dry
- Flexible ink layer conforms to complex surfaces

¹² Some substrates may have inherent odor.

Performance may vary depending on media—for more information, see hp.com/go/mediasolutionslocator or consult your media supplier for compatibility details. For best results, use textiles that do not stretch. Performance varies by printer. For mid-volume HP Latex printers, the optional ink collector is required for porous textiles (included with the HP Latex 850 Printer). For low-volume HP Latex printers, print on media that does not let the ink trespass onto the printer.

¹⁴ HP image permanence estimates by HP Image Permanence Lab. Outdoor display permanence tested according to SAE J2527 on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate, GBC clear gloss 1.7 mil hot laminate, or Neschen Solvoprint Performance Clear 80 laminate. Results may vary based on specific media performance.



HP Latex 260 Printer

Vast improvement in double-sided printing

- The double-sided capability¹⁵ allows you to print double-sided banners with minimal operator intervention; the HP Optical Media Advance Sensor (OMAS) controls registration automatically
- You can also save time—no need to rewind the roll between sides

More textiles and higher quality

- 155-cm (61-in) rolls fully supported; now you have access to more of the fabric rolls available in the market
- Maximize the variety of media you can handle, including soft materials previously too light to load; print on porous materials with the Platen Cover accessory (B2W90A)
- Even higher image quality with the new front tension system and edge holders



Wallcoverings and canvas

Discover a new market opportunity

- Odorless prints¹⁶ meet high environmental standardsideal for hotels, restaurants, schools
- Trial the easy-to-use HP WallArt solution, visit hp.com/ go/wallart17




Temporary textiles18

Complement your business with textile signage applications

- Print on a wide variety of textiles, including uncoated and natural textiles
- An easy-to-use solution compared to dye-sublimation techniques







- GREENGUARD Children & Schools Certified™ HP Latex Inks; produce odorless prints3
- Reduce your impact—print using a range of recyclable HP media, recycle all printing supplies4









- Special ventilation is not required to meet U.S. OSHA requirements on occupational exposure to VOCs from HP Latex Inks. Special ventilation equipment installation is at the discretion of the customer—no specific HP recommendation is intended. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.

 UL ECULOGO Certification to UL 2801 demonstrates that an ink meets a range of stringent criteria related to human health and environmental considerations (see ul.com/EL). HP 792 Latex Ink Cartridges, certification number 11 142 004, certificat by the Eco Mark Office of Japan Environment Association.
- See greenguard.org. Some substrates may have inherent odor.
 Visit hp.com/recycle to see how to participate and for HP Planet Partners program features and availability;
- program may not be available in your area.

Please recycle large-format printing hardware and printing supplies. Find out how at our website

hp.com/ecosolutions

¹⁵ For best results use media options intended for double-sided printing.

Some substrates may have inherent odor.

Requires an HP WallArt account, Internet connection, and connected Internet-capable device. One year free trial license. Cancel at any time. After the free trial, a full HP WallArt license may be purchased. For more information, see hp.com/go/wallart.

Performance may vary depending on media—for more information, see hp.com/qo/mediasolutionslocator or consult your media supplier for compatibility details. For best results, use textiles that do not stretch. Performance varies by printer. For mid-volume HP Latex printers, the optional ink collector is required for porous textiles (included with the HP Latex 850 Printer). For low-volume HP Latex printers, print on media that does not let the ink trespass onto the printer.

Technical specifications

Print speeld	Up to22. 8m ² /hr	(246ff/hr)	
Media	Handling	Rollfeed,take-upreelautomaticutter(for vinylpaper-basednedia, backliptolyester film, and thirbanners)	
	Rollsize	58 to155-cm (23to61-in)rollsup to 40 kg (881b)	
	Rolldiameter	Up to18-cm (7.1-imo)utsidediameter	
	Thickness	Up to 0.5mm (19.7mil)	
Printing	Printim g odes ¹⁹	4-passbidirection22.:8m²/hr (246ft²/hr) 6-passbidirection26.:5m²/hr (178ft²/hr) 8-passbidirection20.:6m²/hr (114ft²/hr) 10-passbidirection20.10m²/hr (97ft²/hr) 12-passbidirection2.10m²/hr (81ft²/hr) 16-passbidirection2.13m²/hr (68ft²/hr)	
	Printesolution Printesolution	n 1200 x 1200 dpi	
	Margins 	Top x bottom x left right5 x 5 x 5 x 5 mm (0. 2x 0. 2x 0. 2x 0. 2in)	
	Printheads 	6 (2x yellow/blac k ,x cyan/lighdyan, 2 x lighnbagenta/magenta)	
	Nozzles	2112 perprinthead2colorsperprinthead, 1056 nozzlespercolor)	
Connectivity	Interfaces (standard)	Gigabi E thernet(1000Base-T)	
Dimensions (w x d x h)	Printer2465 x 69 Shipping2690 x	10 x 1370 mm (97 x 27. 5 x 54 in), 815 x 1200 mm (105. 9x 32. 1 x 47. 2 in)	
Weight	Printer202 kg (4	45 lb)\$hipping291 kg (642 lb)	
What's in the	maintenancekit reelļoadingacce divertensermai	nteprintheadsprinthead leaning it ink cleaning ontaine printestand, take-up essoryedge holderwaste management ntenancekitmaintenanceguide, setupposter, oftware power cords	
Environmental ranges		rature15 to30° ((59to86° F) ture÷25 to55° ((-13to131° F)	
	Operatinghumidi	ity30 to80% RH (non-condensing)	
Acoustic		57 dB(A)(active\$9.5dB(A)(standby) 5B(A)(active\$.;5B(A)(standby)	
Power consumption	2.7kW (printing) 8kW (maximum);50 watts(powersave)		
	Power requirements	Worldwidemodel:Inputvoltage(autoranging) 220 to 240 VAC (-10%+6%), 50/60 Hz (+/-3 Hz), 15 A max perpower cord Japanmodel: Inputvoltage200 VAC (-10%+10%), 50/60 Hz (+/-3 Hz), 15 A max perpower cord	
Certification	Safety	USA and Canada (CSAcertified), EU (LVD and EN 60950-1 compliant)Russia(GOST),China(CCC)	
	Electromagneti	cCompliantwithClassA requirements, including/SA (FCCrules), Canada/CES)/EU (EMC DirectiveAustralia/ACMA),New Zealand (RSM),China(CCC),Japan (VCCI)/Korea (KCC)	
	Environmental	ENERGY STAR, WEEE, EU ROHS, ChinaRoHS, REACH, FEMP, UL	
Warranty	One-vearlimite	blardwarewarranty8-hour,5 daysa week	

Ordering information

Droduot	CQ869A	HP Latex260 61-inPrinter	
Product			
	CR030A	HP Latex260 61-inJapanPrinter	
Accessories	CV063A	HP Designjelt 26500 (61-in Printer2)-in Spindle	
	CV135A	HP Designjelt26500 (61-inPrinterS)-inSpindle	
	CR765A	HP Designje&1-inMediaLoadingAccessory	
	CQ201A	HP Designjett2x500 User MaintenanceKit	
	B2W90A	HP Designjett26500/28500 PlaterCover	
	B8K59A	HP Designjett26500/L28500 Edge Holder	
Original HP printheads	CN702A	HP 792 Yellow/BlackatexPrinthead	
	CN703A	HP 792 Cyan/Ligh C yanLatexPrinthead	
	CN704A	HP 792 LightMagenta/MagentaLatexPrinthead	
Original HP ink cartridge	CN705A	HP 792 775-ml BlackLatexInkCartridge	
	^e <u>en706A</u>	HP 792 775-ml CyanLatexInkCartridge	
	CN707A	HP 792 775-ml MagentaLatexInkCartridge	
	CN708A	HP 792 775-ml YellowLatexInkCartridge	
	CN709A	HP 792 775-ml LightCyanLatexInkCartridge	
	CN710A	HP 792 775-ml Ligh M agenta LatexInkCartridge	
Original HP maintenance supplies	CR278A	HP 792 LatexPrinthea¢leanin≰it	
	CR279A	HP 792 LatexInkMaintenanceKit	
	CH622A	HP 789/792 LatexPrinthea¢leanin€ontainer	
Original HP large format printing materials	HP printimgaterialaredesignedtogethemvithHP LatexInksand HP Latexprintersoprovideoptimalimage quality,onsistencyand reliability.		
	HP PVC-fredWallPaper (FSC⊕and GREENGUARD) Childre& Schools™ Certified) ²⁰		
	HP HDPE Reinforce B anner 🛟 21		
	HP LightTextilBisplaßanner 🛟²¹		
	HP EverydayMattePolypropylen&-irCore\$\frac{1}{2}^2		
	Fortheentir U P LargeFormatPrintin N aterialportfoli p Jease seeglobalBMG.com/hp/signagemedia		
Service and support	HZ644E	HP 3 yearNextbusinessdayDesignjett26500 61-in HardwareSupport	
	HZ645E	HP 3 year4 hour13x5 Designjett26500 61-irHardware Support	
	H7660DE	HP 1 yearPostwarrantyNextbusinessdayDesignjet	

- basedSuprependintingsingfulWidth155 cm/61 in.
- FSC® trademarklicenseodeFSC®-C017543, seefsc. or, lotal FSC®-certified products are availablemal regionsHP PVC-fredWallPaperprinted ithHP LatexInksisGREENGUARD Childred SchoolsCertified.
- ²¹ LargeForHMat Mediatake-backprogram availabilivayiesRecyclingrogramsmay notexist inyourarea.Seehp.com/recycl@ordetails.

For HP Certified third-party RIP solutions, please visit us online at

hp. com/go/Latex260/solutions

See Site Preparation guide requirements to ensure complete compliance with all installation and operation requirements, safety procedures, warnings, cautions, and local regulations. Download this and other manuals fr hp. com/go/Latex260/manuals







HP Latex 260 Printer (formerly the HP Designjet L26500 Printer series)

